



Technical data
 Operation.....electro-hydraulic
 Carrying Capacity.....3000kg
 Working temperature.....-10 °C / +40 °C
 Installation requirements: enclosed area.
Motor
 Power.....2.6 KW
 Voltage.....400V 3ph
 Frequency.....50/60 Hz

| | | | | | | | | | |
|--------------|--------------|----------------|---------------|----------------------------|-------------------|--------------------|--------------|-------------------|---------------------------------------------|
| | | | | XS30N MID RISE LIFT | | | | SPEC-XS30N | |
| 标记 REV | 处数 QTY | 更改文件 CO NUM | 签字 BY | 日期 DATE | 图样标记 PHASE TAG | 数量 QTY | 重量 WEIGHT | 比例 SCALE | Rotary Lift Consolidated (Haimen)Co.,Ltd |
| 设计 DESIGN | 校对 VERIFY | 审核 CHECK | 工艺 TECHNCS | 日期 DATE | | | 1:32 | | |
| | | | | | 共 页 (ALL NO.) | 第 11 页 (SHEET NO.) | | | |
| | | | | | | | | | |

Rotary 品牌未注公差
 角度公差: ±1°
 其他尺寸公差: ±0.8mm (<30.5mm)
 ±1.6mm (>30.5mm)